

# PC Bal Box

**PC Balance Box** eliminates hum problems when connecting audio from your presentation PC. Hum can happen anywhere. You don't have to be running your audio signal a long distance. Power supplies, fluorescent lights and all sorts of equipment can cause noise that is picked up by your audio input cables.

## Main Features

- Stereo/Mono Selection Switch
- 20dB pad switch allows audio to be input on either line or mic connections
- Earth (Ground) Isolation ensures that ground loops are easily defeated
- Left/Right XLR output connectors are standard for live events audio
- Compact size
- No power required (passive) - always ready to go
- Captive lead ensures easy connection every time

## 3 Year Limited Factory Warranty

## Specifications

### Signals:

Typical input 700mVp-p unbalanced stereo audio  
Bandwidth: 200 Hz to 14 KHz Signal levels depend on input level and output impedance

### Control Switches:

Output Pad from -2db / -20dB  
Earth (Ground) lift  
Stereo to Mono

### Connections:

Input: 3.5mm mini stereo jack  
Output: 2 male XLR

### Dimensions mm (inch):

DxWxH: 71(2 8/10") x 64(2 1/2") x 40(1 6/10")  
Captive lead length 1.8m (6ft)

**Weight:** 218g / 8oz

### Customer Supplied Parts:

XLR cables to suit

**Power:** None required

Interspace Industries  
28 High Street, Arlesey, Bedfordshire, SG15 6RA, UK  
call: +44 (0) 870 770 8088, Fax: +44 (0) 870 770 8089  
email: [moreinfo@interspaceind.com](mailto:moreinfo@interspaceind.com) web: [www.interspaceind.com](http://www.interspaceind.com)



## The 'Hum' Eliminator

